

CT75 Controlled Thaw Cabinet CT75



Temperature



Dimensions (mm)



Capacity 75 Chilling (Kg)

Unpacked Weight

Features & Benefits

Controlled Thaw cabinets alternate between circulating gentle heat and refrigeration, via special air ducting and fans, ensuring an even, speedy and safe thaw

- Easy programme selection menu driven dial lets you simply turn to select the programme and push to start
- Thaw food safely from -18/-21°C to +1/+4°C
- Thaw cycle takes approx 7 hours based on maximum capacity and 25mm product thickness
- Overnight storage hold facility, so thawed food is ready for use when you want to use it
- Thaw cabinets alternate between circulating gentle heat and refrigeration, ensuring even and safe thaw

External Finish	
304 Stainless Steel 304 Stainless Steel Rear	Standard Option
For Island Siting	
Internal Finish	
304 Stainless Steel	Standard
Shelving	
GN 2/1 Quantity: 10 Shelf	Standard
Additional Shelf	Option
Base Fittings	
80mm Castors	Standard
150mm Legs	Option

Doors	
Solid Full	Standard
Hinged - Right Hand	Standard
Hinged - Left Hand	Option
Refrigeration	
Forced Air	Standard
Integral	Standard
R134a	Standard
Drain Required?	No

Electrical Data & Service Information		
230 Volts	Standard	
50Hz	Standard	
60Hz	Option	
1 Phase	Standard	
Running Watts	677	
Running Amps	4.3	
Thermal Heat Rejection (W)	842	
Noise (dBa @ 1m)	65	
Fuse Required (A)	13 amp	

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com















Demand more. Choose Foster