



- 3 year warranty
- All models are WRAS approved
- All models use a spray system that minimises scaling and produces separate cubes of crystal clear ice which are slow melting
- Capable of operating in ambient temperatures of between 10°C and 43°C
- Supply water temperature between 3°C and 32°C
- Easy clean ice storage in tough ABS
- All models (except M22-5 13 grams only) are available to special order for the production of cubes of 13 and 33 grams

For maximum production at high ambient temperatures all models are available to special order as water cooled versions at the same price.

## Technical

- Voltage 240V – single phase – 13 amp
- All models supplied with UK 3 pin moulded plug
- Require water supply pressure between 1 and 6 bar
- Optimum ice production is at an ambient temperature of 21°C. Higher temperatures will dramatically reduce ice production

To produce ice of good quality all ice machines must be supplied with suitably softened and filtered water. Any filters and softeners must be of sufficient capacity and correctly maintained.

Model	Production Kgs per 24hrs	Bin Capacity Kgs	Storage Capacity x Standard Cube Size	Dimensions mm W x D x H (inc. feet)	Drain Height (inc. feet) mm	Water Consumption (air cooled) Litres/Kg	Water Consumption (water cooled) Litres/Kg	Price
<b>M22-5</b>	21	5	310 x 13g	345 x 400 x 595	143	4.5	20	<b>£1,040</b>
<b>M30-10</b>	28	10	530 x 18g	390 x 460 x 695	135	5.1	14	<b>£1,280</b>
<b>M34-16</b>	34	16	950 x 18g	500 x 580 x 790	261	3.3	13	<b>£1,450</b>
<b>M42-16</b>	42	16	950 x 18g	500 x 580 x 790	261	4.0	15	<b>£1,600</b>
<b>M50-25</b>	48	25	1470 x 18g	500 x 580 x 900	261	4.0	14	<b>£1,670</b>
<b>M65-40</b>	65	40	2350 x 18g	738 x 600 x 1020	350	2.8	12.8	<b>£2,170</b>
<b>M90-55</b>	90	55	3240 x 18g	738 x 600 x 1120	350	2.5	14.2	<b>£2,510</b>
<b>M130-65</b>	130	65	3830 x 18g	840 x 740 x 1175	355	2.8	15.3	<b>£3,190</b>
<b>M155-65</b>	155	65	3830 x 18g	840 x 740 x 1175	355	2.6	13	<b>£3,520</b>