

# Bottle Coolers



ZXS2



ZX1



ZX2



ZXS3



ZX3

## FEATURES

- \_\_\_\_\_ Laminated exterior and interior
- \_\_\_\_\_ Internal illumination
- \_\_\_\_\_ Wider spaced finned condenser for minimum maintenance
- \_\_\_\_\_ Locks as standard
- \_\_\_\_\_ Can be built in
- \_\_\_\_\_ Double glazed door
- \_\_\_\_\_ Single door models have reversible door
- \_\_\_\_\_ Adjustable feet
- \_\_\_\_\_ Replaceable door gasket

## TECHNICAL SPECIFICATIONS

- \_\_\_\_\_ Controller: Digital controller with temperature display
- \_\_\_\_\_ Cooling: Fan assisted
- \_\_\_\_\_ Defrost: Automatic
- \_\_\_\_\_ Refrigerant: R134a
- \_\_\_\_\_ Climate Class 4
- \_\_\_\_\_ Temperature Range: +4°C ~ +12°C
- \_\_\_\_\_ Power Supply: 13amp

MODEL	FINISH	DOOR	CAPACITY (Bottles*)	EXTERNAL DIMENSIONS (H x W x D mm)	POWER CONSUMPTION	WEIGHT (kg)	RRP
ZX1	Charcoal with black door	1	144	900 x 600 x 520	325W	70	
ZX2		2	218	900 x 900 x 520	350W	100	
ZX2-SL		2 (sliding)	218	900 x 900 x 520	350W	100	
ZX3		3	324	900 x 1350 x 520	425W	132	
ZXS1	Charcoal with anodized aluminium framed door	1	144	900 x 600 x 520	325W	70	
ZXS2		2	218	900 x 900 x 520	350W	100	
ZXS3		3	324	900 x 1350 x 520	425W	132	

\* based on 275ml bottles

Note: minimum height without feet is 880mm

