


Ventilated Gastronorm Glass Door Refrigeration

2/1 Gastronorm Capacity

BR1SSCR



BR models - suitable for fresh meat storage



BF2SSCR



FEATURES

- High grade 304 stainless steel exterior & interior
- Internal corners rounded to aid cleaning
- 4 adjustable shelves GN2/1 per door
- Double glazed door
- Self closing door(s) with dwell position
- Single door models have reversible door
- LED lighting
- Suitable for fresh meat storage (BR range)
- Lock fitted as standard
- Heavy duty castors as standard
- Replaceable door gasket

TECHNICAL SPECIFICATIONS

Controller:	Dixell controller
Cooling:	Ventilated
Defrost:	Automatic
Refrigerant:	R290
Climate Class:	4
Power Supply:	13amp

MODEL	DOOR	TEMPERATURE RANGE	GROSS CAPACITY	EXT. DIMENSIONS (H x W x D mm)	POWER CONSUMPTION	DECIBELS	WEIGHT (kg)	RRP
BR1SSCR	1	-2°C ~ +8°C	650L	2010 x 740 x 858	215W	60dBA	136	
BF1SSCR	1	-15°C ~ -18°C	650L	2010 x 740 x 858	480W	60dBA	141	
BR2SSCR	2	-2°C ~ +8°C	1300L	2010 x 1480 x 858	440W	60dBA	213	
BF2SSCR	2	-15°C ~ -18°C	1300L	2010 x 1480 x 858	780W	60dBA	226	

