



## SL422L32N0 -

When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A free standing Super Easy 422 offers outstanding value with no compromise in quality or performance.

- ✓ Outstanding quality with no compromise in quality or performance.
- ✓ Mechanical thermostat maintains oil to within +/-8 °C of the temperature selected.
- ✓ Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- ✓ Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- ✓ Supplied with separate oil buckets.

### Specifications

| Summary              |                                   | Power and Performance |            |
|----------------------|-----------------------------------|-----------------------|------------|
| Brand                | FriFri                            | Total Power kW        | 2 x 7.5    |
| Range                | Super Easy                        | Temperature Range °C  | 95-190     |
| Power Type           | Electric                          | IP Rating             | IPX4       |
| Unit Type            | Free-standing                     | Temperature Control   | Mechanical |
| Available in UK Only | No                                |                       |            |
| UK Warranty          | 2 Years Parts and Labour Warranty |                       |            |
| Export Warranty      | Contact your local dealer         |                       |            |
| GTIN                 | 5056105123606                     |                       |            |

| Key Specifications |                  | Capacity                |                               |
|--------------------|------------------|-------------------------|-------------------------------|
| Number of Baskets  | 2                | Product Output per Hour | 2 x 17kg fries - 7mm [frozen] |
| Number of Tanks    | 2                | Capacity Litres         | 2 x 7.5-9.0                   |
| Gravity Filtration | No               |                         |                               |
| Pumped Filtration  | No               |                         |                               |
| Drain Location     | Through the body |                         |                               |

| Weights and Dimensions    |       | Supply Connections             |                                       |
|---------------------------|-------|--------------------------------|---------------------------------------|
| Unit Height (External) mm | 986   | Requires Installation          | Yes                                   |
| Unit Width (External) mm  | 397.5 | Requires Electrical Supply     | Yes                                   |
| Unit Depth (External) mm  | 650   | UK 3 Pin Plug                  | No                                    |
| Net Weight Kg             | 75.5  | Requires Hardwiring            | Yes                                   |
|                           |       | Electrical Supply Rating Watts | 2 x 7,500                             |
|                           |       | Three Phase Amps               | L1=2 x 10.9; L2=2 x 10.9; L3=2 x 10.9 |
|                           |       | Three Phase Voltage            | 400                                   |
|                           |       | Number of Supply Cables        | 2                                     |

| Shipping         |     |
|------------------|-----|
| Packed Weight Kg | 82  |
| Packed Height cm | 113 |
| Packed Width cm  | 79  |
| Packed Depth cm  | 52  |

## Available Options

### Legs/Castors

**OC200**

OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front]

**OC400**

OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]

**Lincat Limited**

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of

**Customer Care****Tel:** +44 1522 875500**Email:** care@lincat.co.uk**Export Customers****Tel:** +44 1522 875536**Email:** export@lincat.co.uk**Opening Hours****Monday – Friday:**

8.30am – 5pm