



## SL422H32N0 - FriFri Super Easy 422 Electric Free-standing Twin Tank Fryer without Filtration - 2 Baskets - W 400 mm - 2 x 11.0 kW

When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A free standing Super Easy 422 offers outstanding value with no compromise in quality or performance.

- ✓ Outstanding quality with no compromise in quality or performance.
- ✓ Mechanical thermostat maintains oil to within +/-8 °C of the temperature selected.
- ✓ Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- ✓ Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- ✓ Supplied with separate oil buckets.

### Specifications

#### Summary

<b>Brand</b>	FriFri
<b>Range</b>	Super Easy
<b>Power Type</b>	Electric
<b>Unit Type</b>	Free-standing
<b>Available in UK Only</b>	No
<b>UK Warranty</b>	2 Years Parts and Labour Warranty
<b>Export Warranty</b>	Contact your local dealer
<b>GTIN</b>	5056105122760

#### Power and Performance

<b>Total Power kW</b>	2 x 11.0
<b>Temperature Range °C</b>	95-190
<b>IP Rating</b>	IPX4
<b>Temperature Control</b>	Mechanical

#### Key Specifications

<b>Number of Baskets</b>	2
<b>Number of Tanks</b>	2
<b>Gravity Filtration</b>	No
<b>Pumped Filtration</b>	No
<b>Drain Location</b>	Through the body

#### Capacity

<b>Product Output per Hour</b>	2 x 20kg fries - 7mm [frozen]
<b>Capacity Litres</b>	2 x 7.5-9.0

#### Weights and Dimensions

<b>Unit Height (External) mm</b>	986
<b>Unit Width (External) mm</b>	397.5
<b>Unit Depth (External) mm</b>	650
<b>Net Weight Kg</b>	56

#### Supply Connections

<b>Requires Installation</b>	Yes
<b>Requires Electrical Supply</b>	Yes
<b>UK 3 Pin Plug</b>	No
<b>Requires Hardwiring</b>	Yes
<b>Electrical Supply Rating Watts</b>	2 x 11,000
<b>Three Phase Amps</b>	L1=2 x 15.9; L2=2 x 15.9; L3=2 x 15.9
<b>Three Phase Voltage</b>	400
<b>Number of Supply Cables</b>	2

#### Shipping

<b>Packed Weight Kg</b>	59.95
<b>Packed Height cm</b>	113
<b>Packed Width cm</b>	79
<b>Packed Depth cm</b>	52

## Available Options

### Legs/Castors

**OC200**

OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front]

**OC400**

OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]

**Lincat Limited**

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of

**Customer Care****Tel:** +44 1522 875500**Email:** care@lincat.co.uk**Export Customers****Tel:** +44 1522 875536**Email:** export@lincat.co.uk**Opening Hours****Monday – Friday:**

8.30am – 5pm