



SL622H32G0 - FriFri Super Easy 622 Electric Free-standing Twin Tank Fryer with Filtration - 2 Baskets - W 600 mm - 2 x 15.0 kW When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A free standing Super Easy 622 offers outstanding value with no compromise in quality or performance.

- Outstanding quality with no compromise in quality or performance.
- Mechanical thermostat maintains oil to within +/-8
 °C of the temperature selected.
- Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- Keeping your oil in peak condition! Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri© filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes – so easy there is no excuse not to!
- Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- Optimum Allergy Control. Supplied with separate oil buckets, and can be supplied with separate pumped filtration systems, providing completely segregated gravity filtration for optimum allergen control or to cater for dietary preferences.

Specifications

Summary		Power and Performance	
Brand	FriFri	Total Power kW	2 x 15.0
Range	Super Easy	Temperature Range °C	95-190
Power Type	Electric	IP Rating	IPX4
Unit Type	Free-standing	Temperature Control	Mechanical
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105122814		
Key Specifications		Capacity	
Number of Baskets	2	Product Output per Hour	2 x 26.5kg fries - 7mm [frozen]
Number of Tanks	2	Capacity Litres	2 x 12.5-14.5
Gravity Filtration	Yes		

Pumped Filtration

Drain Location

No

Through the body

Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	986	Requires Installation	Yes	
Unit Width (External) mm	592	Requires Electrical Supply	Yes	
Unit Depth (External) mm	650	UK 3 Pin Plug	No	
Net Weight Kg	98.5	Requires Hardwiring	Yes	
		Electrical Supply Rating Watts	2 × 15,000	
		Three Phase Amps	L1=2 x 21.7; L2=2 x 21.7; L3=2 x 21.7	
		Three Phase Voltage	400	
		Number of Supply Cables	2	

Shipping

Packed Weight Kg	87.45
Packed Height cm	113
Packed Width cm	79
Packed Depth cm	72

Available Options			
Oil Pump			
OP1	1 Oil Pump		
OP2	2 Oil Pumps		
Baskets			
622_2_BASKETS		2 Baskets	
622_3_BASKETS		3 Baskets	
622_4_BASKETS		4 Baskets	
Legs/Castors			
OC200	OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front]		
OC400	0C400 - 4 Castors[2 Fixed at Rear + 2 Swivel at Front]		
Available Accessories			

FZ301093

SMALL BASKET FOR 311 - COMPLETE WITH HANDLE

Lincat fift

Lincat Limited

Whisby Road, Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm