

SPECIFICATION SHEET

NYLON

PRODUCT CODE	NYM
BASE SHELF MATERIAL	Mild Steel
FINISH	Silver grey thermoplastic powder coating applied via a fluidised bed. Food Contact certified.
USES	General catering storage, Dry storage, Refrigeration, Freezer, Retail displays.
WIDTHS AVAILABLE	300mm, 400mm, 450mm, 500mm, 600mm
LENGTHS AVAILABLE	600mm, 800mm, 900mm, 1000mm, 1100mm, 1200mm, 1300mm, 1500mm, 1800mm
WEIGHT LOADING	Up to 900mm – 150Kgs per shelf 1000mm – 140Kgs per shelf 1100mm – 135Kgs per shelf 1200mm – 110Kgs per shelf 1300mm – 100Kgs per shelf 1500mm – 90Kgs per shelf 1800mm – 75Kgs per shelf
POST OPTIONS	1700mm as standard (other heights available) Stainless steel Post also available
FEET	Standard supply Bolt foot, (Glide Feet and castors also available).
FEATURES & OPTIONS	'S' Hooks for continuous bay and ninety degree angled units Base Frame & Infill Shelves available
CLEANING	Cleaning should be undertaken using general purpose cleaning agents and may be pressure washed or steam cleaned. Castors may not be power washed or steam cleaned. Always read the label of the detergents to verify suitability with the product finish

- All weight loadings assume even load distribution across the shelf and are based on a 5% deflection of the centre of the shelf
- Maximum weight loading per bay is 800Kgs for a static bay, assuming bottom shelf is 70mm from the floor
- For mobile bays on standard castors the maximum weight loading is 240Kgs assuming a 3 point load and 80Kg per castor
- All shelf dimensions are shown as Nominal Width and Lengths, for actual widths subtract 9mm and for actual length subtract 34mm

